

Painter's Plus CAULK



Titebond® Painter's Plus is a high-quality, versatile siliconized acrylic caulk that is designed for both interior and exterior applications. It offers an excellent flexible, air-tight, water-resistant seal. Painter's Plus provides a strong bond to most common building materials, including wood, metal, glass, masonry, aluminum and brick. It is ideal for sealing joints, repairing cracks and back-filling gaps. Titebond Painter's Plus is de-aired for a smooth, uniform bead that extrudes and tools easily. It can be painted with a water-based paint with one coat and will not bleed through the paint. Titebond Painter's Plus is a non-stringing formula that won't sag or drool and it has excellent bead cut-off. It also cleans up with water when wet.

Ready to Use

No mixing or primer required;
reduces labor and installation cost

Ultra Low VOC

VOC-compliant in all 50 states

Joint Movement

Remains flexible

Weather Resistant

Produces long-lasting weather-tight seals

Paintable

May be painted with premium grade water-based
paints 2-4 hours after application

Wide Temperature Application Range

40°F – 120°F

Ideal Applications Include:

- Tubs
- General interior/exterior crack repairs
- Showers
- Sinks
- Back-filling gaps

INTERIOR

PAINTER'S PLUS CAULK

SPECIFICATIONS

Complies with the following requirements:

- ASTM C834 Type OP Grade -18°C (white & colors)
- ASTM C834 Type C Grade 0°C (clear)

PHYSICAL AND CHEMICAL CHARACTERISTICS

Type: Acrylic	Paintable: 2-4 hours
Non-reactive VOC: <i>white:</i> 23 g/L (< 1.5%) <i>colors:</i> 21 g/L (< 1.5%) <i>clear:</i> 5 g/L (< 1.5%)	Tack-free time: 2-3 hours
Tooling time: 10-15 minutes	Solids: <i>white:</i> 82% <i>colors:</i> 87% <i>clear:</i> 60%
Full cure: 3-7 days*	
Weight per gallon: <i>white:</i> 13.5 lbs. <i>colors:</i> 14.02 lbs. <i>clear:</i> 8.8 lbs.	
Freeze thaw stability: Stable	
Flashpoint: Solvent free/Not applicable	
Application temperature: 40°F – 120°F	
Joint movement capability: Flexible	
Storage life: 24 months in tightly closed containers at 50°F to 80°F.	
Coverage: 10.1 fl. oz. = 31 linear ft. at a 1/4" bead	
Clean-up: Soap and water	

* Cure will be affected by joint size, configuration and environmental conditions.

40 Year Limited Warranty: If not satisfied with product performance when used as directed, return container and proof of purchase to Franklin International, Inc. for replacement of product. Liability is limited to product replacement only.

APPLICATION

Titebond® Painter's Plus comes ready to use. Apply by professional cartridge gun. Extrude sealant into openings, gaps or holes surrounding the application. Fill joint opening to maximum capacity and repeat as necessary. If joint depth exceeds 1/2", use backing material. If necessary, smooth bead immediately with a damp sponge. Painting may occur 2-4 hours after application with a premium grade water-based (latex-based) paint. For other paint types, a compatibility test is recommended. It is the sole responsibility of the user to thoroughly test any proposed use with all substrates to determine project suitability.

LIMITATIONS

Do not apply if rain is expected within 12 hours. Titebond Painter's Plus should be dry to the touch and ready to paint in 2-4 hours. Painter's Plus is not designed for continuous submersion or use below the waterline. For questions, please call our Help Line at 1.800.347.4583 or visit us at Titebond.com.

CAUTION STATEMENT

WARNING: EYE, SKIN AND RESPIRATORY IRRITANT. The white option contains acrylic polymer, limestone, titanium dioxide, ethylene glycol and mineral derivatives. The clear option contains acrylic polymer and ethylene glycol. The remaining color options contain acrylic polymer, limestone, titanium dioxide and ethylene glycol. Long term exposure to ingredients in these products can increase the risk of certain cancers. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate personal protective equipment. **FIRST AID:** If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush eyes with water for 15 minutes; contact physician. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Part Number	Size/Color	Weight	UPC	Units Per Package	Units Per Pallet
8301	10.1 oz. Cartridge/White <i>8 colors available</i>	14.82 lbs.	037083083019	12	108

Franklin International

Sales: 1.800.669.4583 / Technical: 1.800.347.4583 ©2016 BCM 5/16 FF1019

TITEBOND.COM

